

# Jarvis Powdercoated



## **Powdercoated MDF top**

Our powdercoated MDF (Medium Density Fiberboard) desktop is made of wood fibers and is as environmentally friendly as it is strong, meeting strict European standards for the use of Volatile Organic Compounds and off-gassing. The powdercoating process results in a slightly textured, seamless, glareless surface that emits no VOCs and resists scratches, water, and stains. It's also lightweight so requires less fuel for shipping.

## **Frame**

The Jarvis frame has an industry-leading 350 lb. lifting capacity and we offer two desk range options: Extended Range and Mid-Range. Our mid-range option doesn't go as low or high, but works for 85% of adult heights. Heavier steel feet and a lifting column that's wider at the bottom means a more grounded desk.

# Jarvis Powdercoated

## Top specs

- Thickness: 3/4"
- Core material is medium-density fiberboard
- Surface is scratch-resistant, VOC and formaldehyde-free thermotech powder coat

## Top options

- Color: white, black, graphite
- Rectangle or contour
- 30" x 27", 42" x 27" [rectangle only with center grommet holes] 48" x 30", 60" x 30", 72" x 30", 78" x 30" [rectangle & contour options available with grommet holes]
- Grommet holes for tops 48" and larger are positioned on the back left and right edges of the desk (near where your computer might be). Tops 42" and smaller will come with a single back centered grommet hole.
- The drilled openings are circular and measure 80 mm (approximately 3.15") in diameter.
- Covers are available in Black or White.
- We also offer powered grommets, which are also available in black or white.
- Our powered grommets include one AC outlet, one USB-C and one USB-A port, so you can plug in up to 3 devices per grommet. You can upgrade zero, one, or both of your grommets.

## About Powdercoat

- Powder coating, is thicker and more durable than paint
- Applied using a dry, zero-formaldehyde process - doesn't leach harmful chemicals into the environment.
- Powder coating process results in a slightly textured, seamless, glareless surface

## Standards/Certifications

- Meeting strict European standards for the use of Volatile Organic Compounds (VOC's) and off-gassing
- VOC's are natural gasses/particles released by materials. Every tree in a forest releases VOC's
- Off Gassing happens when chemicals are releasing unwanted/unhealthy gasses - like the smell in a new car
- SFI® Sustainable Forestry Initiative - Certified Sourcing - View Certificate
- California Air Resources Board (CARB) - ATCM 93120 - View Certificate
- Eco-Certified Composite (ECC) Standard 4-11 - Environmentally Responsible Use of Wood Fiber - View Certificate
- LEED® US Green Building Council - New Construction and Major Renovations
- Green Globes® Rating System - New Construction and Major Renovations
- ICC 700-2015 National Green Building Standard™ - Resource Efficiency, Indoor Environmental Quality, and Remodeling

## Care & use

- Do use a coaster for both hot and cold beverages.
- Avoid extended exposure to standing liquids.
- Clean surface with a soft cloth, warm water, and very mild soap. Over time, mild soaps can accumulate on the surface and cause damage to the finish. Be sure to wipe and dry thoroughly after cleaning.
- Be cautious not to expose the surface to harsh chemicals or cleaners. These types of products can quickly damage the finish: rubbing alcohol, cleaners with bleach, acetone etc.
- Protect the top surface. It is recommended that you utilize a mousing surface and refrain from writing directly on the top to keep wear on your Powder Coat MDF top to a minimum.

## Frame

- Frame color options: black, white, silver, alloy
- Powder coated frame
- Narrow: recommended for tops 26" - 47" and Wide: recommended for tops 44" - 82"
- Mid-range Jarvis Frame: Height adjustable from 26.5" to 45.75" (without top)
- Extended-range Jarvis Frame: Height adjustable from 23.75" to 49.25" (without top)
- Mid-range Frame: Adjustment speed of 1.3" per second with soft start/stop
- Extended-range Frame : Adjustment speed of 1.5" per second with soft start/stop
- 350 lb lifting capacity (inclusive of top weights)
- Adjustable foot leveling studs for uneven flooring (0.25" adjustment)
- Operating noise less than 50dB
- Frame: JIS grade G 3141 SPCC cold rolled steel
- [Industry-leading warranty](#): 7 years on all frame, mechanical, and electrical components

## Handset

- Simple Up/Down handset: 2.35" wide x 1.15" tall
- Programmable Memory handset: 5.7" wide x 1.25" tall

## Electrical specs

- Voltage: Input 110v / Output: 31V
- Transformer power: 200W (0.2 on standby)
- Power supply current 5 amps